



80 YEARS
1939 - 2019

GLB + Smart Electric Car Charging Stations for Cloud Billing with OCPP



Futuresmart

Features across the range:

Plug and Play means installers can either simply connect and walk away, or easily configure the charger to:

- Delivers 3.7kW or 7.4kW
- Accepts inputs to start or stop charging
- Provide remote isolation

Dynamic Load management (DLM) protects the main fuse in an installation by reducing the Electric Vehicle charging current when the total load is high and by increasing the charging current when the total load is low.

DLM requires a kWh meter (at the main distribution board) connected by a Beldin screened twisted pair cable (Modbus protocol) to the charger.

DC leakage Monitoring built in. This extremely important feature ensures that the protective devices operate under fault conditions and negates the need for a Type B RCD.

Both the LAN and 4G modem models offer full OCPP communication to back office systems, billing and vehicle with OCPP1.5OAP, OCPP1.6SOP and 1.6JSON

System overview

- Comprehensive 3 year warranty
- 2 models provide full range
- Make your installation EV Ready with GLB Box
- Main Fuse protection - DLM
- Full mode 3 change control
- Control - up to 32 GLB's linked as master/slave configuration
- Type 2 connector
- Power 7.4 kW
- Simple and intuitive installation
- LED Status information of the charger
- DC leakage built in, no need for separate Type B RCD

Main Features

- Automatically takes power from a PV system if available
- Motorised interlock with power reserve
- Future proofed, update of firmware and software
- Mounting on either a wall or pillar
- Plug & Play installation
- IK08 & IP44

Recommended Locations for Installation

- Work Places
- Car Parks
- Hotels
- All installations where OCPP or full cloud billing is required



ECONOMY OF USAGE

Don't overpay - save!



SIMPLICITY OF USAGE

User-friendly product



COMMUNICATION AND CONTROL

Remote management of up to 32 Devices



AVAILABLE CONNECTORS

2 types of connectors Type 1 & Type 2

Technical details

Charger power (power input)	Max 1x7.4kW
Standards/directives	IEC 61851-1, 61851-22 and IEC TS 61439-7 CE
1 phase power supply, power supply parameters	Max. 3F; 230V / 400V 50Hz
Electrical Protection Device	type A or type B RCD and circuit breaker
Installation system	TT, TN And IT system (S marking for TT and TN system)
Charging type/security class/Toughness	Mode-3
Available connectors	1 x Type2 socket (version with socket) / 1 x Type 2 / Type 1 plug (version with cable)
Working temperature range, IP/IK	IP44 / IK08 / -25° to 40°C
Mounting/height of mounting	Wall-mounting (inside/outside) / 0.5 - 1.5m from the ground level to the lower edge of the charger
Dimensions	422/205/124mm
Weight	1- phase with socket of 3.2kg
Communication	OCPP1.5OAP, 1.6SOAP, 1.6JSON



Office for
Low Emission
Vehicles

seai SUSTAINABLE
ENERGY AUTHORITY
OF IRELAND

Wall Mounted Charger

GLB-DC-LAN-PLUS	7.4kW Socket type 2 with full OCPP & DC Monitoring	LAN
GLB-DC-MC-PLUS	7.4kW Socket type 2 with full OCPP & DC Monitoring	4G
GLB-EV READY	EV Ready Empty GLB Enclosure	



Accessories

Back Office	OCPP Billing Solution
ST-GHL	GLB Mounting Pillar



Birmingham & Belfast | +44 (0)121 716 1510 | www.garo.co.uk
 Dublin | +353 (0)1 866 5360 | www.garo.ie
 Sweden | +46 (0)370 33 28 00 | www.garo.se

GARO®

The GARO group pursue a policy of continuous development and improvement of its products. This brochure is not an offer within the meaning of the law, and the manufacturer reserves the right to change the technical parameters of the offered equipment without prior notice.